



SCHMERSAL Tech Briefs:

NEW RSS260 Compact RFID Safety Sensor



Features



2 actuator approach directions



3 Color LED Display
Green: Power, not actuated
Yellow: Actuation
Red: (Flashing) Diagnostic error


Actuator options



RST-260-1
(39 mm x 29.5 mm x 18 mm)



RST-16-1
(60 mm x 16 mm x 6.8 mm)



RST-U-2
(23 mm x 9 mm x 7 mm)

Overview

Schmersal has applied Radio-frequency identification (RFID) technology in the RSS260 series non-contact safety sensor. The RSS260 is designed for application in safety circuits monitoring the position of hinged, sliding or removable guards using a specifically coded, passive RFID tag in the actuator.

The clear advantage of using RFID technology is enhanced tamper resistance. Since the RSS260 uses a special frequency, the sensor will disregard non-actuator RFID signals, and the passive RFID tag in the actuator will not interfere with other RFID systems such as product trackers. The RSS260 is also difficult to by-pass because it has the option of individual coding: The basic version of the sensor responds to any RST target actuator; The "I1" version only accepts the coded ID number of the specific target actuator which is taught in during the first start-up; The "I2" version allows the teach-in process to be repeated, allowing replacement of a lost or damaged actuator.

The non-contact sensing allows for longer switch life - Since there are no moving parts there is little to no wear on the components. As safety guard panels age, the sensor will also tolerate misalignments, up to 10 mm.

The RSS260 series has several actuator targets and accepts two approach directions which allow for mounting flexibility. The standard actuator (RST-260-1) matches the body profile of the switch which fits to regular aluminum profile systems, the RST-16-1 has a flat elongated profile with a discrete appearance for mounting on clear plastic doors, and the RST-U-1 is an extremely compact rectangular target designed for integration into the surrounding construction of the guard door. Any of these targets can approach the sensor from either the front face or the long side.

The RSS260 also features all of the diagnostic advantages of our other electronic safety sensors and solenoid interlocks. It comes standard with LEDs to indicate various errors. For more advanced indication the RSS260 is also available with serial diagnostics to communicate its status via serial data packages for use in various network protocols. Because of an integrated dual monitoring microprocessor, only one switch is required to meet PLe per ISO 13849-1 and SIL3 per IEC 62061. The RSS260 can be connected in series with other electronic sensors and locking switches, up to 31 devices, without loss of signal or safety level when monitored with a standard Schmersal safety controller.

Flexible mounting options



Side actuation with RST-260-1

Flat, discrete RST-16-1 mounted to Plexiglas door

RST-U-1 embedded into sliding Plexiglas door

Applications

- Material handling systems
- Packaging machinery
- Chemical processing equipment
- Robot cells
- Folding or brake presses
- Filter presses
- Punching machines
- Printing machines
- Injection molding
- Palletizers
- Packaging equipment

Available Literature



RSS260 Brochure
4 pages

Ordering Details

RSS260①-②-ST

- ① Actuator Coding
blank Standard version (no coding)
I1 Individual coding (single)
I2 Individual coding (multiple)
- ② Outputs
D Diagnostic output
SD Serial Diagnostic

Regularly stocked models:

RSS260-D-ST RSS260-SD-ST
RSS260-I2-D-ST

Accessories

Actuators

RST-260-1 Standard Actuator
RST-16-1 Flat Actuator
RST-U-2 Compact Actuator

Mounting / Spacers

ACC RSS260-SK Mounting hole seal
ACC RSS260-MK Mounting set

Connector cables

with straight connector
A-K8P-M8-S-G-2M-BK-2-X-A-4
A-K8P-M8-S-G-5M-BK-2-X-A-4
A-K8P-M8-S-G-10M-BK-2-X-A-4

with right angled connector
A-K8P-M8-S-W-2M-BK-2-X-A-4
A-K8P-M8-S-W-5M-BK-2-X-A-4
A-K8P-M8-S-W-10M-BK-2-X-A-4

CSS-Y-8P Y adapter
CSS-Y-A-8P Chain end

V-SK8P-M12/M8-S-G-2M-BK-2-X-A-4
Double headed cable for Y
adapter connection, 1 meter

Compatible Safety Controllers

SRB-301MA SRB-301MC
SRB-301ST-24 SRB-301LCB
SRB-504ST SRB-211ST
SRB-324ST SRB-031MC

Bold part numbers are regularly stocked

Contact

Schmersal USA
660 White Plains Road
Suite 160
Tarrytown, NY 10591
Tel: 914-347-4775
Fax: 914-347-1567
E-mail: salesusa@schmersal.com

Schmersal Canada
15 Regan Road
Unit #3
Brampton, ON L7A 1E3
Tel: 950-495-7540
Fax: 905-495-7543
E-Mail: salescanada@schmersal.com