# SCHMERSAL Tech Briefs: AZM200 Solenoid Interlock with Door Handle



### Features



Door handle actuator options Standard handle (G1) 2. Rotary knob (G2)



Optional inside emergency releases 1. Standard handle (P1)

- 2. Inset rotary (P25)
- 3. Heavy duty metal assembly (P20)



Optional integrated lockout device on door handle is one of three methods for lockout Actuator retracts into door handle housing when opened (handle is horizontal)



3 color LEDs for signaling: Green = Power Yellow = Status Red = (Flashing) Diagnostic error

### Overview

The AZM200 is a combination of solenoid interlock and electronic safety sensor with a door handle actuator.

The AZM200 Series is designed for machine/work cells where access to a hazardous work area must be controlled until safe conditions exist. The solenoid lock provides 506 pounds of force to secure the machine guard until dangerous conditions, which may exist immediately after removal of power, have abated. The solenoid lock may be controlled by a time delay, motion detector, position sensor or other suitable component.

One unique design feature of the AZM200 is the door handle actuator. When the guard is opened, the actuator is retracted into the handle housing, protecting the actuator and the operator against damage and injury.

The door handle actuator is available with an optional inside emergency release which meets ANSI/RIA R15.06 requirements. This one hand operated handle mechanically overrides the solenoid lock from inside the hazardous area, allowing operators to leave quickly and safely - even during a power failure.

The AZM200 also features an integrated electronic safety sensor to detect guard door closure independently of the solenoid lock. This sensor uses our patented pulse echo technology, a non-contact operating principle that limits wear on components, and tolerates misalignment. A microprocessor provides continuous internal function tests and monitors the safety outputs, meeting PLe to ISO13849-1 and SIL 3 to IEC61508, even when using one switch per guard or wiring them in series.

Three color LEDs on the sensor indicate status, various errors, and misalignment. For more advanced indication the AZM200 is also available with serial diagnostics to connect to commercial field bus systems.

The slim housing of the switch was designed to match the aluminum profiles used in many machine guard doors

The AZM200 series are cULus and CE approved to meet stringent North American and European Standards.

### **Solenoid controls**

The BDF200 series control stations are designed to offer various machine or process controls conveniently located at the guard door in a housing that matches the AZM200. Each BDF200 control station can include operators in up to 4 positions which can be configured to user-defined application needs, including a readily accessible integrated Emergency Stop palm button meeting RIA 15.06 requirements.



### Available Literature

### Robot cells

Applications

- Food processing machinery
- Pharmaceutical machinery
- Medical applications
- Material handling systems
- Packaging machinery
- Chemical processing equipment
- Folding or brake presses
- Filter presses
- Punching machines
- Printing machines
- Injection molding
- Palletizers
- Packaging equipment



**GK-1 Safety Products Catalog** AZM200: pages 1-54 thru 1-59

## **Ordering Details**

### Solenoid switch/sensor AZM200002-T-34

1	Monitoring	
	blank	Guard locking monitored
	В	Actuator monitored
2	Connection	n
	SK	Screw terminals
	CC	Cage clamps
	ST1	M23, 9 pole connector
	ST2	M12, 8 pole connector
3	Outputs	
	1P2P	Diagnostic output
	1P2PW	Closed & locked output
	SD2P	Serial Diagnostic
4	Locking	
	Blank	Power to unlock
	A	Power to lock

### **Door handle actuator** AZ/AZM200-B30-0TA23-4

1	Direction	
	L	Left hinged door
	R	Right hinged door
2	Handle Types (outside)	
	G1	Handle
	G2	Rotating knob
3	Emergency Exit (inside)	
	blank	Without
	P1	Red Door handle
	P20	Red metal handle
	P25	Inset rotary knob
	P30	3 point locking bar
_	P31	3 point with exit handle
4	Integrated	Lockout Device
	Blank	Without
	SZ	With lockout (3 lock)
Ac	ressories	

### Accessories

Lockout device
Lockout device
Mounting plate
Mounting plate
Mounting plate

#### **Compatible Safety Controllers** SRB-301MA SRB-301MC

SRB-301ST-24 SRB-301LCB SRB-504ST SRB-211ST SRB-324ST SRB-031MC Bold part numbers are regularly stocked

Contact

### Schmersal USA

660 White Plains Road Suite 160 Tarrytown, NY 10591 Tel: 914-347-4775 Fax: 914-347-1567 E-mail: salesusa@schmersal.com

Schmersal Canada

15 Regan Road Unit #3 Brampton, ON L7A 1E3 Tel: 950-495-7540 Fax: 905-495-7543 E-Mail: salescanada@schmersal.com

